

SAFETY DATA SHEET

Vulcan P RFU (HSE No.:7437)

Page 1 of 4 Revision No. 3

Issue date: 19 December 2006

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product name Vulcan P RFU

Company PelGar International Ltd

Unit 13, Newman Lane Industrial Estate, Newman Lane, Alton, Hampshire

GU34 2QR

Telephone Tel +44 (0) 1420 80744

Telefax Fax +44 (0) 1420 80733

Product code 102

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components Permethrin 0.25% CAS 52645-53-1 Xn; R20/22 R43 N; R50/53

Piperonyl Butoxide 0.75% CAS 51-03-6 N; R50/53 Tetramethrin 0.125% CAS 7696-12-0 N; R50/53 Petroleum Distillates Hydrotreated Light Oil 90-100%

CAS: 64742-47-8 Xn;R65

3. HAZARDS IDENTIFICATION

Most important hazards Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment. Harmful: may cause lung damage if swallowed.

Specific hazards Product can accumulate static charges which can cause an incendiary electrical discharge.

Material can form flammable mixtures or can burn only if heated to temperatures at or above

the flash point.

4. FIRST AID MEASURES

Skin contact Remove contaminated clothing Wash off immediately with soap and plenty of water. If irritation

persists obtain medical attention. Contaminated clothing should be washed and dried before re-

use

Eve contact Rinse immediately with plenty of water for at least 15 minutes. If irritation persists obtain

medical attention

Inhalation Inhalation of mist or spray, may cause irritation of the respiratory system. Move to fresh air.

Obtain medical advice immediately.

Ingestion Do not induce vomiting. If conscious give a small amount of milk or water to drink and obtain

medical attention. Show the container label or this safety data sheet to the doctor

General advice In the case of accident or if you feel unwell, seek medical advice immediately (show the label

where possible).

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Keep fire exposed containers cool by spraying with water if exposed to fire. Fight surrounding

fire with foam, dry chemical, water spray or mist.

Extinguishing media which must not be used for safety reasons

Do not use water jets

Specific hazards Combustible material. Fire may cause toxic fumes (oxides of carbon) to evolve. Avoid spraying

water directly into storage containers due to danger of boilover.

Vulcan P RFU

Page 2 of 4 Revision No. 3

Issue date: 19 December 2006

Special protective equipment for firefighters

In the event of fire, wear a self-contained breathing apparatus and a chemical protection suit,

gloves and boots.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Wear suitable protective clothing, gloves and eye/face protection..See section 8. Keep public

away.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Contain or absorb leaking liquid with earth or sand. Prevent liquid entering watercourses, sewers or basements. Prevent product from entering drains. If substance has entered a watercourse or sewer or contaminated soil or vegetation,

inform the appropriate authority.

Methods for cleaning up Soak up with inert absorbent material. Transfer to a suitably labelled container. Subsequently,

wash the contaminated area with water, or detergent and water, taking care to prevent the washings from entering surface water drains. For large spills, recover by pumping (use an

explosion proof or hand pump).

7. HANDLING AND STORAGE

Handling

Material will accumulate static charge, which may cause an electrical spark (ignition source). Take precautionary measures against static discharges Do not apply in the presence of naked flames, hot surfaces or unprotected electrical equipment. Ensure all equipment is electrically grounded before beginning transfer operations Container remains hazardous when empty. Continue to observe all precautions. The product is flammable but not readily ignited. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition - No smoking.

If splashing is likely to occur wear approved eye protection. If spray mists are likely, wear a suitable approved respirator.

If skin contact is likely to occur wear rubber gloves and suitable impervious protective clothing. Use in a well ventilated area where possible. Always use good personal hygiene procedures when handling chemicals. Do not smoke eat or drink while handling this product. Wash hands, face and exposed skin after using, and before eating, drinking or smoking. Read the label before use.

Keep product and empty container away from heat and sources of ignition.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Keep away from food and animal feedstuffs Store in accordance with Health and Safety Executive's Guidance Note HSG71 Keep away from oxidising agents Keep away from sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limit(s) Petroleum Distillates Hydrotreated Light Oil

TWA(ppm):300

Engineering measures The use of mechanical (explosion proof) dilution ventilation is recommended whenever this

product is used in a confined space.

Respiratory protection Suitable approved respirator if exposed to spray mists

Hand protection Rubber or plastic gloves

Eye protection If splashes are likely to occur, wear goggles

Skin and body protection Impervious clothing boots

9. PHYSICAL AND CHEMICAL PROPERTIES

Description Liquid

Colour Light yellow

Odour Aromatic

pH Not applicable

Boiling point/range 200 - 250°C

Vulcan P RFU

Page 3 of 4 Revision No 3

Issue date: 19 December 2006

Flash point >70°C

Explosive properties 0.6 - 8.0%

Vapour pressure 0.03kPa at 20C

Relative density

Immiscible @ 20C Water solubility

Viscosity No data

Vapour density >1

Not available Melting point/range

>200C **Autoignition temperature**

10. STABILITY AND REACTIVITY

Stability Stable under normal conditions.

Conditions to avoid Heat, flames and sparks.

Materials to avoid Strong oxidising agents strong bases

Hazardous decomposition

products

Oxides of carbon, smoke

11. TOXICOLOGICAL INFORMATION

Acute toxicity ORL RAT LD50 > 2000 mg/kg (calculated)

DERMAL RAT LD50 > 4000mg/kg (calculated)

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Vapour concentrations above recommended exposure levels

might be irritating to eyes and the respiratory tract.

Sensitisation May cause sensitisation of susceptible persons by skin contact.

Repeated or prolonged

Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation

exposure

mutagenic effects

of susceptible persons.

Not available

carcinogenic effects Not available

12. ECOLOGICAL INFORMATION

Ecotoxicity effects Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Further Information This product must not enter water discharge system. Inform appropriate authority if large spillage

enters drains.

13. DISPOSAL CONSIDERATIONS

General Information Dispose of as hazardous waste in compliance with local and national regulations.

Contaminated packaging Dispose of as unused product.

14. TRANSPORT INFORMATION

ADR/RID

UN-No 3082 Packing group III Class 9 Hazard ID 90

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (contains permethrin and tetramethrin)

IMO

UN-No 3082 Packing group III Marine pollutant No Class 9

EmS F-A S-F

Vulcan P RFU

Page 4 of 4 Revision No. 3

Issue date: 19 December 2006

IATA-DGR

UN-No 3082 Packing group III Class 9 Sub-risks -

packaging 914

15. REGULATORY INFORMATION

Symbol(s): Xn - Harmful; N - Dangerous for the environment

X_n¥

R-phrase(s) R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65 - Harmful: may cause lung damage if swallowed.

S-phrase(s)To avoid risks to man and the environment, comply with the instructions for use.

S23 - $Do\ not\ breathe\ fumes/vapour/spray.$

S24 - Avoid contact with the skin.

S36/37/39 - Wear suitable protective clothing, gloves and eye/face protection. S60 - This material and its container must be disposed of as hazardous waste.

S61 - Avoid release to the environment. Refer to special instructions/safety data sheets. S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this

container or label.

16. OTHER INFORMATION

Text of R phrases R20/22 - Harmful by inhalation and if swallowed. **mentioned in Section 2** R43 - May cause sensitization by skin contact.

R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65 - Harmful: may cause lung damage if swallowed.

Recommended restrictions Insecticide for professional use only.

Sources of key data used CHIP 2002 to compile the datasheet EH40

Raw material suppliers Safety Data Sheets.

Replaces Revision No.: 2. Changes to Section 2. Changes in classification of piperonyl butoxide.